

COSTA RICAN SEISMIC CODE: CONSIDERATIONS ON THE REDEFINITION OF THE DESIGN SPECTRA IN VIEW OF RECENT SEISMIC DATA

G. Santana ¹ and J. Gutiérrez ²

ABSTRACT

Some comments on the earthquake engineering development in Costa Rica are given. A description of the newly started Strong Motion Instrumentation Program is given. The description includes remarks on both free field strong motion recording stations as well as instrumented buildings. Also, a description of the current norm for determination of lateral forces due to earthquakes is given. Some comments are also offered as to the appropriateness of using high ductility ratios for certain structural systems.

INTRODUCTION

Safeguarding life and property from the destructive effects of earthquakes is a major worldwide problem. In spite of the increased awareness of this problem, earthquakes each year claim many lives and cause enormous damage to man-made structures and other facilities. In order to design safe, economical structures and facilities in earthquake prone regions of the world, it is necessary to understand the nature of the ground motions that these systems may be expected to experience during their lifetimes. It is equally important to understand the behavior of the materials from which these structural systems are made as well as the interaction between the different structural elements in the system.

The purpose of every seismic design regulation should then be that of preserving human life and reducing the socioeconomic impact of strong ground motions. However, it is necessary to bear in mind that design regulations only represent a lower bound approximation to the problems of safe construction. Furthermore, it should be realized that design codes are continuous processes that only represent the state of knowledge, or the lack of it, at a certain stage of the development of the profession. Many lessons have been learned from every earthquake and many more will continue to be learned.

SEISMICITY IN CENTRAL AMERICA

Central America is located in a region of high seismicity. Figure 1 shows a map of the seismicity of Mexico and Central America for the period 1962-1969. The entire isthmus is contained in the so-

¹ Director, Earthquake Engineering Laboratory, Engineering Research Institute, 2060 University of Costa Rica, Costa Rica.

² Research Professor, Earthquake Engineering Research Institute, 2060 University of Costa Rica, Costa Rica.

called Caribbean Plate. The western border of this plate coincides with the Pacific coast line of the isthmus. There, the Cocos Plate is sliding under the Caribbean Plate. The origin of many of the larger earthquakes in the region can be traced to this subduction zone. In the most defined areas of the subduction zone, earthquakes have been found to have hypocenters between 50 and 100 Km deep.

There are also earthquake of lower magnitude that occur inside the volcanic arc. They may not be called intraplate ground motions but nevertheless, they are shallow and of low magnitude and have usually affected smaller areas.

The most destructive earthquakes in the region in the last two decades have the second type of origin mentioned above. These are, San Salvador in 1964 and in 1986 and Managua in 1972. All these events have been associated with local faults in the intermountain valleys of volcanic and alluvial origin. In the case of San Salvador in 1964 and Managua in 1972, the cities sustained heavy damage due to poor construction methods, particularly in the low income housing sectors. Once again in 1986, San Salvador suffered heavy damage in the adobe and baharaque construction. However, it is important to note that there was considerable damage in a good number of modern buildings. Most regrettable of all was the damage to important facilities like hospitals and clinics. All except one of these facilities suffered enough damage to put them out of operation at the most critical time.

Guatemala suffered an earthquake in 1976 due to the strike slip fault between the Caribbean Plate and the North American Plate. Lifelines and important large buildings were damaged during this event.

EARTHQUAKES IN COSTA RICA

Costa Rica is de fifth republic of the former Central American Confederation. It occupies the southernmost portion of the isthmus. As with the rest of Central America, there are two main causes for strong ground motion. The first one is the subduction zone and the second one is the faulting associated with the volcanic arc.

The data about past earthquakes goes back to about 400 years. The reconstruction of the seismic history for the country has been through the newspaper accounts as well as through recollections from the local authorities. The most recent damaging earthquakes that have occurred in this century were the 1910 and 1911 Cartago Earthquakes, the 1924 Orotina Earthquake and most recently the Tilaran Earthquake of 1973.

The Cartago Earthquakes and epicenters within 20 Km of the capital city, San Jose. They caused the collapse of a great number of masonry and adobe constructions. The causative fault was identified as a local fault and the rupture length was a about 10 to 15 Km. The magnitudes of the shocks were estimated at around 5.5 to 6 in the Richter scale. The events are very significant because in spite of their low magnitude, they could prove to be a bigger threat than the much

larger tectonic ground motions. The characteristics of the near field events of moderate magnitude have not fully been determined. An excellent opportunity of gaining some insight into the subject was presented by the large number of records obtained during the San Salvador Earthquake of 1986.

The Earthquake in Orotina in 1924 has an unclear origin. It is believed to have been caused by an undefined and transitional area of the subduction zone towards the central portion of the Pacific Coast of Costa Rica. There is little information on the effects of the motions because of the lack of population in the epicentral area. According to the newspapers of the date there was significant bending in the rail road connecting San José with Puntarenas, the most important Pacific port and moderate damage to constructions in the west end of the Central Valley.

The Tilarán Earthquake in 1973, was due to a local fault in the Northwestern part of the country. It caused moderate damage to the church in the local town. It also caused damage in most of the one story concrete block housing and extensive landslides.

The first attempt to regulate the construction to make it safe against earthquakes came after the Cartago Earthquakes. Adobe construction was banned, and bahareque and thick masonry became the most widely used materials. Those first recommendations included the utilization of a tying beam on the top of masonry walls for one story housing. In essence the observed damage in the earthquakes was the sole basis of the seismic design recommendations. Later on, the provision for the application of a lateral load equivalent to 10 percent of the local weight of the structure was added. The code was seldom enforced and as a result disappeared into oblivion.

The Managua Earthquake of 1972 was the cause of considerable concern among the Costa Rican civil engineering community. As it is often the case, in the first few months after the earthquake, several initiatives for the prevention of a disaster of similar magnitude in Costa Rica got under way. The most significant of them all was the establishment of a Permanent Seismic Code Commission. It was charged with the task of drafting a Seismic Design Code intended to regulate all civil engineering construction. The first edition of the Code was put in use in 1974.

Together with the effort of drafting a Seismic Code, a National Seismological Network was implemented with the cooperation of the University of Costa Rica and the National Institute for Electricity.

Another two major seismic motions occurred in the subsequent years. In 1978 a magnitude 7.0 earthquake was felt off the coast in the northern portion of the Pacific shore. In 1983, a magnitude 7.2 earthquake shook the southern portion of the Pacific coast.

This time the epicenter was inland. However, the level of damage in the city of San José was higher than in the epicenter region. There was collapse of cladding in several buildings and cracking of some columns in corners of structures with soft stories.

STRONG MOTION INSTRUMENTATION PROGRAM

Soon after the Golfito Earthquake of 1983, the Engineering Research Institute of the University of Costa Rica initiated installation of a strong motion instrumentation program. The main objective of the program is to obtain basic information for the design of earthquake resistant structures. The program had the initial support of the United States Agency for International Development, the University of California at Santa Cruz, as well as the Government of Costa Rica. At present the Program is being supported solely by the University of Costa Rica.

The Strong Motion Program operates 19 Recording Stations distributed throughout the country. The maps in figures 2a and 2b show the location of the stations. The central cluster of stations in the city of San José is depicted in its entirety.

The siting of the different stations was based on the Seismic Risk Study for Costa Rica performed by Morgart et al. in 1977. It has been revised several times after the first lay out of the siting criteria. Figure 3 to 6 show the maximum acceleration maps for return periods of 50, 100, 500 and 1000 years proposed in the above mentioned study. The maps for the higher return periods show the assumption of fundamentally three seismic sources for the territory. All of these seismic sources go along the Pacific coast. Figure 2a shows the location of the seven recorded ground motions since the installation of the network. There appears to be an indication of agreement between the location of the epicenters and the proposed risk maps. Other important sources like the one mentioned above in the Central Valley of the country have shown higher seismic activity along local faults during last year.

The typical cross section of the subduction fault is shown in figure 7. The suggested disposition of strong motion instrumentation along this type of fault is one of parallel lines of instruments as it is indicated in the figure. The chosen disposition of the strong motion stations tries to follow the same pattern. However, the density of the array falls somewhat short of the suggested level. The average suggested distance between the stations is 20 Km on each of three lines following the fault. The current density of the array is about twice that amount and in some portions it gets closer to triple the amount.

The instrumentation in the Central Valley is more random in nature. There, the principal objective has been more to instrument buildings. The objective here is to facilitate response studies that could lead to improved understanding of the dynamic behavior and the potential for damage to structures under seismic loading. There are currently four multi-story buildings instrumented in the city of San Jose. A typical diagram of the instrumentation performed in those buildings is given in figure 15. The chosen arrangement has been to locate one instrument in the basement or ground floor and then one in the top floor. They are kept in the same vertical line as much as possible. The problems of torsional motion cannot be measured with this instrumentation. Hence, the instruments are kept as close as possible to the center of rigidity of the structure, usually the elevator core. The buildings have been chosen to have the most diverse qualities in view of the budget constraints. The structures are made out of steel, light weight concrete, reinforced concrete

and they have the two most used structural arrangements: moment resisting frame and combined frame-wall resistant structure.

Table 1 indicates the location of every strong motion recording station. These locations are given by instruments. So, the first two accelerographs show the same coordinates since they belong to the same station. On Table 2 the orientation of the instruments is given so as to permit the identification of the maximum acceleration components in a ground motion.

The largest event recorded so far by the network was registered on July, 1987. There were three seismic events on the same day and within a radius of about 35 Km. The range of magnitudes in the Richter scale was of 4.0 to 4.4, the body wave magnitude reached 5.0 on the largest event. Figure 9 shows the Modified Mercalli intensity map for the first recorded event, denominated Quepos1, the figure also shows the locations of the triggered instruments in the network. The pattern seems to suggest directivity of the signal in the north direction. The closest station to the epicenter did not triggered. After thoroughly checking the instrument it was concluded that it was in proper working condition during both events. It is unfortunate that the network did not have more stations between the origin point and the cluster of stations in the Central Valley.

During this events an apparent amplification of the signal was recorded in two nearby stations in San Jose. Figure 11 shows the recorded ground motions in the ICE and Hatillo Stations respectively. It is interesting to notice that even though the stations are only 2Km apart the peak accelerations for the Hatillo Station more than double the ones recorded at ICE. Truly, for a low level excitation like the one at hand it would be adventurous to make any definite statements about the phenomena. However, it does call for a closer observation in future events. Table 3 shows the values of all the recorded peak accelerations for both Qepos1 and Qepos2 events.

The next stage in the development of the Strong Motion Instrumentation Program contemplates the installation of five new stations. The projected growth includes the construction of two more stations along the Pacific shore at intermediate points from the existing ones, a station on a rock site near the city of San Jose, a station in the Caribbean coast and finally a station at an intermediate distance between the Pacific shore and the city of San José. With the new station it is hoped that a better understanding of the source mechanism, attenuation conditions as well as the wave propagation characteristics from the subduction zone will be attained.

Another important projected development of the program contemplates the installation of a local array for measuring the effects of surface geology in the seismic motion in the Central Valley. Figure 8 shows the typical configuration of such an array for a wide valley such as the one under consideration. The configuration proposed will only include three instruments; one downhole set on rock at about 45 m depth, another one located directly above the first one at surface and a third one approximately 600 m apart on a rock outcrop. Adequate instrumentation to achieve the objectives of the experiment should be

- a. Triaxial instruments
- b. Accurate relative timing
- c. A sample rate of at least 100 sps.
- d. A band width of least .1 - 25 Hz.

Investigation of site geometry, velocity of bedrock, material properties for soft soil deposits including data from several bore holes is currently under way.

Also currently under way is a study of active faults in the Central Valley of the country. This is a much needed work that will help improve the location of the strong motion recording stations.

RECOMMENDED PROVISIONS FOR BUILDING CONSTRUCTION

The present revision of the Costa Rican Seismic Code (CSCR-86) is based on the designation of a Seismic Force Coefficient SFC for each projected building. Such coefficient is used to determinate the total base shear applied to the structure as a result of the earthquake action. The total base shear force is then obtained as a fraction of the total weight of the structure, i.e.

$$\text{Total Base Shear} = \text{SFC} \times \text{Total Weight} \quad (1)$$

As in the case of the U.S. code standards (SEAOC, ATC, UBC, etc.), there is not a clear agreement on the number of parameters on which the seismic force coefficient should depend. Neither is there a clear idea of what parameter or combination of parameters is most appropriate to measure the level of damage that can be attributed to the seismic excitation. The traditional idea has been to utilize the maximum ground acceleration as a measure of the level of damage expected in an earthquake. The rationale of this assumption being that the destructive potential is all due to the inertial forces excited during the ground motion. However, observation of earthquake response of buildings in different parts of the world seem to indicate that the correlation between level of damage and maximum ground acceleration is not very good. (Ang, 1988; Derkiureghian, 1988; McCabe, 1987).

The SFC used in the provisions depends ultimately on the following parameters

- Linear Dynamic Characteristics of Structure; i.e., natural periods of vibration, structural damping.
- Type of Supporting Soil; i.i., rock, stiff soil, soft soil.
- Expected Maximum Level of Ground Acceleration
- Structural Ductility.

The maximum level of ground acceleration is obtained from the maps of isoacceleration showed in figures 3 through 6. Thus, the maps amount to a seismic zonation for the country on the basis of return periods of 50, 100, 500, and 1000 years. The determination of the return period for a certain

building is based on the expected life span for the structure as well as on the probability of exceedance of a certain acceleration level. The graphs have a very strong dependency on the reliability of the attenuation curves used for the country as well as the wave propagation characteristics for the different types of paths encountered. For this particular topic the code continues to be based in the study of Morgart et. al.

The weight of the structure is calculated as the dead weight plus 15% of the live load as a minimum.

The rest of the parameters are summarized in figures 12, 13 and 14 in the form of curves for Dynamic Amplification vs. Period for soft soil foundation with respect to rock or stiff soil foundation. For periods longer than .4 seconds the increment on the coefficient could be as high as 100% when comparing soft soil to rock location for a period of 1.0 seconds.

The structural ductility is defined as a function of the resisting structural system. Table 2.4.1 of the code shows this requirement as well as the proposed structural damping associated with each structural type.

For buildings that are classified as regular in plan and elevation and seven or less stories of 30m or less above ground level, the calculation of the fundamental period is facilitated by the following empirical formula:

$T = 0.12N$ Steel Frame Building

$T = 0.10N$ Reinforced Concrete Frame Building

$T = 0.08N$ Reinforced Concrete Frame Wall Building Steel Braced Frame Building

$T = .05N$ Reinforced Concrete Structural Wall Building.

Where:

T = Fundamental Natural Period in Seconds

T = Total number of stories.

This formula is used as a first approximation to the period of the structure. In a second stage, the period must be recalculated using the elastic displacements resulting from the response of the structure when subjected to the seismic loads acting statically at each floor level. The periods should be calculated using the following equation

$$T=2\pi \sqrt{\frac{1}{g} \frac{\sum_{i=1}^N W_i (\delta_i^e)^2}{\sum_{i=1}^N F_i \delta_i^e}} \quad (2)$$

Where

δ_i = Elastic displacement at level i due to seismic forces

$F_i = C\eta$

C = Seismic coefficient

$$\eta = \frac{\sum_{k=1}^N W_k h_k}{\sum_{k=1}^N W_k h_k^2}$$

For more general buildings, a dynamic modal analysis is required. The number of modes to be used in such procedure is taken a one fourth of the number of degrees of freedom. The modal responses are then combined using the square root of the sum of the square method. An indication is given to provide for better modal combination when the system has coupling modes.

The code also provides an upper bound for the expected level of drift in a building. For each type of resisting structural system, the total horizontal displacements as well as the relative story displacements are estimated for the inelastic range as follows.

$$\begin{aligned} \delta_i &= K\delta_i^e \\ \Delta_i &= K\Delta_i^e \end{aligned} \quad (3)$$

Where

δ_i = Total horizontal inelastic displacement at level i

Δi = Relative inelastic displacement for level i

K = Inelastic displacement factor given in table 2.8.1

δ_i^e, Δ_i^e = Elastic displacement

The non-structural components on the building must be separated from the resisting system using the previous calculations.

The drift limitation in the code is given in terms of the relative interstory displacement. The corresponding values for the different types of resisting structural systems are given in table 2.8.2 the norm.

CONCLUSIONS

The efforts on designing structures against earthquakes has been a continuing process. It has been mentioned that the efforts of providing the designers with adequate provisions has been a task undertaken since 1972. However, the understanding of the effects of earthquakes is not by any means completed. The current norm is likely to be modified by the measurement of motion characteristics for the different regions of the country. A new seismic risk study that could include a larger data based is needed. It is also necessary to provide some form of verification to the assumptions made on the behavior of the materials currently used in common construction. The current version of the code does not make a clear distinction between member ductility and structural ductility. The ductility requirements are rather high for type 5 resisting structural system. However, it must be said that the drift provision takes care of this deficiency in an indirect manner.

May it be added that Costa Rica, as any underdeveloped country is facing a harsh economic situation. As the population increases the resources become more scarce. The problem of providing housing for every citizen is therefore becoming more acute. Hence, investigation on new building materials, new resisting structural systems, and new construction techniques is a high priority. Bearing this in mind, it should be stated that the proposed solutions to the housing problem must be durable.

REFERENCES

1. Gutiérrez, J., "Código Sísmico de Costa Rica. 1986", Editorial Tecnológica de Costa Rica, Cartago, Costa Rica, 1987.
2. Morales, L. D., "Las zonas Sísmicas de Costa Rica y Alrededores", Revista Geológica de

América Central, No. 3, San José Costa Rica, 1985.

- 3 Mortgart, C. P., Zutty, T. C., Shah, H. C. & Lubetkin, L., "A Study of Seismic Risk for Costa Rica", The John A. Blume Earthquake Engineering Center. Stanford University, Report No 25, April 1977.
- 4 Santana, G., Altamirano, J. L. & Vargas, W., " Acelerogramas Registrados Durante los Sismos de Quepos del 15 de julio de 1987", Instituto de Investigaciones en Ingeniería, Informe INII- 39-87, Universidad de Costa Rica, September 1987.

TABLE 1

Location of Strong Motion Recording Stations

NO.	SERIE	LOCALIZACION	FECHA DE INSTALACION	COORDENADAS		ALTITUD (msnm)
				LATITUD N	LONGITUD W	
1	5733	Bco Nal (5)	11-oct-85	09:56'14"	84:04'55"	1145
2	5579	Bco Nal (17)	10-oct-85	09:56'14"	84:04'55"	1200
3	5585	Aurola (5)	15-nov-85	09:56'17"	84:04'38"	1145
4	5735	Aurola (16)	15-nov-85	09:56'17"	84:04'38"	1190
5	5728	INS (5)	28-aug-85	09:56'18"	84:04'31"	1140
6	1728	INS (P 12)	15-may-85	09:56'18"	84:04'31"	1185
7	5581	ICE (5)	09-oct-85	09:57'25"	84:06'15"	1125
8	5729	San Pedro	17-apr-84	09:56'18"	84:03'02"	1200
9	5732	Hatillo	29-may-85	09:54'59"	84:05'53"	1130
10	5576	Cartago	10-apr-84	09:52'02"	83:55'31"	1445
11	5730	Tecnológico	17-Apr-84	09:51'32"	83:54'46"	1400
12	5578	Cachi	10-apr-86	09:50'32"	83:48'19"	1000
13	5582	San Isidro	06-Mar-85	09:22'25"	83:42'27"	705
14	5584	Golfito	07-mar-85	08:38'41"	83:10'19"	10
15	5727	Quepos	21-may-85	09:25'54"	84:09'59"	5
16	5726	San Ramón	19-nov-84	10:05'13"	84:29'00"	1120
17	5731	Puntarenas	08-aug-85	09:58'36"	84:45'02"	10
18	5580	Santa Cruz	06-aug-84	10:17'16"	85:35'35"	45
19	5583	Liberia	22-jan-86	10:37'10"	85:27'37"	120
20	5734	Alajuela	12-mar-86	10:01'07"	84:12'59"	950
21	5577	Recope	28-sep-87	09:53'42"	83:56'26"	1560
22	2025	Geología UCR	30-sep-87	09:56'22"	84:03'16"	1200

TABLE 2**Orientation of Strong Motion Instruments**

No	SERIE	LOCALIZACION	LONG	ORIENTACION	
				VERT	TRANSV
1	5733	Bco Nal (5)	S 82:00 E	Arriba	N 08:00 E
2	5579	Bco Nal (17)	S 08:00 E	Arriba	N 82:00 E
3	5585	Aurola (5)	S 85:00 W	Arriba	S 05:00 E
4	5735	Aurola (16)	S 85:00 W	Arriba	S 05:00 E
5	5728	INS (5)	N 10:00 E	Arriba	N 80:00 W
6	1728	INS (P 12)	N 07:00 W	Arriba	S 83:00 W
7	5581	ICE (5)	S 75:00 E	Arriba	S 15:00 E
8	5729	San Pedro	S Franco	Arriba	E Franco
9	5732	Hatillo	S Franco	Arriba	E Franco
10	5576	Cartago	S Franco	Arriba	E Franco
11	5730	Tecnológico	S Franco	Arriba	E Franco
12	5578	Cachi	S Franco	Arriba	E Franco
13	5582	San Isidro	S Franco	Arriba	E Franco
14	5584	Golfito	S Franco	Arriba	E Franco
15	5727	Quepos	S Franco	Arriba	E Franco
16	5726	San Ramón	S Franco	Arriba	E Franco
17	5731	Puntarenas	N 85:00 E	Arriba	N 05:00 W
18	5580	Santa Cruz	S Franco	Arriba	E Franco
19	5583	Liberia	S Franco	Arriba	E Franco
20	5734	Alajuela	S Franco	Arriba	E Franco
21	5577	Recope	S Franco	Arriba	E Franco
22	2050	Geología UCR	S Franco	Arriba	E Franco

TABLE 3

Peak Acceleration Values Recorded During the Quepos Events of 15 July, 1987.

NOMBRE DEL SISMO	MAGNITUD (ml)	ACELEROGRAFO SERIE UBICACION SMA-1	ACEL. PICO		
			L (%G)	V (%G)	T (%G)
Quepos 1	4.3	5732 Hatillo	7.20	1.00	7.10
		5733 Bco Nal (S)	1.10	1.60	1.70
		5579 Bco Nal (P 17)	1.1	2.1	2.2
		5576 Cartago	5.8	3.6	4.6
		5730 Tecnológico	5.9	2.8	7.6
		5735 Aurola (P 16)	1.0	2.1	2.0
		1728 INS (P 12)	3.0	3.8	2.2
		5728 INS (S)	2.8	1.0	2.8
		5581 ICE (S)	2.7	2.4	3.0
		5726 San Ramón	1.6	1.1	2.1
Quepos 2	4.4	5732 Hatillo	5.0	1.0	6.0
		5576 Cartago	4.2	2.1	4.1
		5733 Bco Nal (S)	1.4	1.1	1.7
		5579 Bco Nal (P 17)	0.9	1.6	1.4
		5735 Aurola (P 16)	2.1	2.6	1.5
		1728 INS (P 12)	2.0	3.3	1.7
		5581 ICE (S)	2.7	1.2	3.2
		5726 San Ramón	1.1	1.1	2.1




FIGURE 1 Seismicity of Mexico and Central America 1962 - 1969.




Figure 2a. Location of Strong Motion Recording Stations.

SAN JOSE




Figure 2b. Location of Strong Motion Recording Stations in the José Metropolitan Area.




Figure 3. Maximum Acceleration Map for 50 year Return Period, as % of g.



Figure 4. Maximum Acceleration Map for 100 year Return Period, as of % of g.




Figure 5. Maximum Acceleration Map for 500 year Return Period, as % of g.




Figure 6. Maximum Acceleration Map for 1000 year Return Period, as % of g.




FIGURE 7 Typical Source Mechanism and Wave Propagation Array for Subduction Thrust Fault.




FIGURE 8 Typical Simple Extended Array Configuration for Wide Valley.





FIGURE 9 Modified Mercalli Intensity Map and Epicenter Location for the Quepos-1 Event of 15 July 1987






FIGURE 10 Modified Mercalli Intensity Map and Epicenter Location for the Quepos-2 Event of 15 July 1987



L

S 75° E

V

Arriba

T

N 15° E

No. Registro: 22
 Serie: 5581 Ubicac: ICE (S)
 Sismo: Quepas (1) Fecha: 15/07/87
 Mag: 4.3 D. Epic: 51.32 Prof. 48.0
 Acel. Pico L. 2.7 V. 2.4 T. 3.0



L

S Franco

V

Arriba


T

E Franco

No. Registro: 14
 Serie: 5732 Ubicac: Hatillo
 Sismo: Quepas (1) Fecha: 15/07/87
 Mag: 4.3 D. Epic: 47.04 Prof. 48.0
 Acel. Pico L. 7.2 V. 1.0 T. 7.1


FIGURE 11 Accelerogram Records Obtained at ICE and Hatillo Stations in the City of San Jose

**Figure 12 Dynamic Amplification Factor
for Rock Site**




According to CSCR-86

**Figure 13 Dynamic Amplification Factor
for Hard Soil Site**




According to CSCR-86

**Figure 14 Dynamic Amplification Factor
for Soft Soil Site**



According to CSCR-86



**Figure 15 Instrumentation
for a Multi-Story Building**